



AUSTRALIAN TECHNICAL RUBBER

TOP DECK DRILL RIG FLOORING

THIS IS THE ULTIMATE IN DRILL RIG PLATFORM FLOORING
THE FLOOR IS MADE FROM PREMIUM GRADE POLYURETHANE WITH A
NON SLIP CRUMB RUBBER TOPPING AND A 1020 STEEL BASE .
THESE FLOOR EXHIBITS OUTSTANDING ABRASION, IMPACT
AND CHEMICAL RESISTANCE, ALONG WITH HIGH LOAD BEARING CAPACITY.
ALL FLUIDS WILL DRAIN FROM THE FLOOR WITHOUT COMPROMISING GRIP

SPECIFICATION

COLOR	BLACK , YELLOW, BLUE
WATER ABSORPTION	NONE
WEIGHT	115KG -M/2
UV STABILITY	GOOD
ABRASION RESISTANCE	VERY GOOD
DIMENSIONS	1000x1000 & 1100x 1200 50 MM THICK WATER CUT TO ANY SIZE OR SHAPE
LIFTING POINT FITMENT	M16x2 CAN BE BOLTED THROUGH OR WELDED FROM UNDERSIDE

POLYURETHANE

	PTMEG POLYETHER POLYOL
HARDNESS	95 SHORE A
TENSILE STRENGTH	6500
100% MODULUS	1900 PSI
300% MODULUS	2600 PSI
ELONGATION	375%
TEAR STRENGTH	140
COMPRESSION SET	
22HRS @ 70 C	35
SPECIFIC GRAVITY	1.13

CRUMBED RUBBER

HARDNESS	EPDM 70 SHORE A
-----------------	----------------------------

STEEL

	1020 MILD STEEL 304 STAINLESS STEEL
--	--

